

II. SPECIFICATION AMENDMENTS

1. Please insert the following headings and sub-headings prior to page 1, line 1 as written below:

RECEPTACLE AND PLUG CONNECTORS

BACKGROUND OF THE INVENTION

1. Field of the Invention

2. Please insert the following sub-heading between page 1, line 16, and page 1, line 17 as written below:

2. Prior Art

3. Please insert the following heading between page 1, line 25, and page 1, line 26 as written below:

SUMMARY OF THE INVENTION

4. Please insert the following heading between page 2, line 23, and page 2, line 24 as written below:

BRIEF DESCRIPTION OF THE DRAWINGS

5. Please insert the following heading between page 3, line 8, and page 3, line 9 as written below:

DETAILED DESCRIPTION OF THE INVENTION

6. Please insert the following heading and sub-heading prior to page 8, line 1 as rewritten below.

CLAIMS

What is claimed is:

7. Please insert the following new page 11 after page 10 as written below.

ABSTRACT

A receptacle connector (1) for a mobile telephone or the like comprises a housing (3) of insulating material, a shielding (4), and a plurality of contact terminals (5). Channels (13) extend parallel to the lateral sides (11) between the front and backsides (9, 10) and the contact terminals are made as strip like elements mounted in these channels. At least some of the contact terminals each are provided with two retention parts (14,15) having a width greater than the width of the channels providing a retention force mainly parallel to the upper and lower sides. The contact terminals (5) each are provided with a butt-mount contact end (16) and a tail end (17), wherein the retention part at the tail end has a width greater than the width at the butt-mount contact end. A plug connector (34) for interconnecting a mobile device to a stationary device, comprises a housing (36) of insulating material, a shielding (44), a plurality of contact terminals (39) mounted in the housing, at least one latch element (55) to latch the plug connector in a

receptacle connector (1) of the mobile device, and a button (60) to operate the latch element. The housing of the plug connector is provided with at least one locating peg (51) to be received in a chamber (51') of the receptacle connector.